




DIN / ISO	ASTM / UNE / OTHER	AJAX	CATERPILLAR	CUMMINS	DRESSER-RAND	JENBACHER	MWM (CATERPILLAR ENERGY SOLUTIONS)	ROLLS-ROYCE SOLUTIONS (MTU)	TEDOM	WÄRTSILÄ	WAUKESHA	OTHER
-----------	--------------------	------	-------------	---------	--------------	-----------	------------------------------------	-----------------------------	-------	----------	----------	-------



HDAX 9500 SAE 40							TA 1000-1109 for fuel class B (biogas, sewage gas) & C (landfill gas) engines: Type 2 & 3, Type 4 A, Type 4 B/D and Type 6 C/E		61-0-0281.1 for fuel types G (natural gas), P (propane/butane), L (landfill), B (biogas) & S (sewage gas)			MAN Truck & Bus M 3271-5
HDAX 9300 SAE 40			CG gas engines; G3500H gas engine sets [^]				TA 1000-1108 for fuel class A engines: Type 9 (all versions); TA 1000-1109 for fuel class A engines: Type 2 & 3, Type 3 F, Type 4 C/E, Type 6 C/E, Type 6 F/J and Type 6 G/H/K	TCG series gas engines				Bergen Engines all engine types in natural gas operations
HDAX 9200 Low Ash Gas Engine Oil SAE 40			CG gas engines type CG260, CG170 & CG132; TALE engines type G3516 E+ [^] & G3516 [^]				TA 1000-1109 for the following fuel class A engines (including those fitted with an oxidation catalytic converter): Type 2 & 3, Type 4 A, Type 4 B/D, Type 4 C/E, Type 6 C/E and Type 6 F/J; Special gas applications (fuel class S)	TCG series gas engines	61-0-0281.1 for fuel types G (natural gas) & P (propane/butane)	Cogeneration applications		Aggreko Jenbacher JMS 420 gas engines (B & C ranges used by Aggreko) RMB/Energie natural gas operations
HDAX 8200 SAE 40			CG gas engines type CG260, CG170 & CG132				TA 1000-1109 for the following fuel class A engines: Type 2 & 3*, Type 4 B/D*, Type 4 C/E*, Type 6 C/E* and Type 6 F/J*; Natural gas, associated petroleum gas, mine gas & biogas [sulphur < 200 mg/10 kWh] engines	TCG series gas engines	Series 4000 gas engine models L61, L62, L63, L64, L64-FNER, T24-N & M05-N			Bergen Engines types K, C & B
HDAX 7200 Low Ash Gas Engine Oil SAE 40			Series G3600* & G3500* engines; CG gas engines type CG260 [^] , CG170 [^] & CG132 [^]		Category I*, II* & III*		TA 1000-1109 for the following fuel class A engines: Type 2* & 3*, Type 4 A/B* and Type 6 C/E*	TCG series gas engines [^]	Series 400 gas engines running on natural gas or propane; Series 4000 gas engine models L61, L62, L63 & L64 running on natural gas [^]	Wärtsilä*	Cogeneration applications	Bergen Engines* Deutz TR 0199-99-01213 (913, 914 & TCG 2015 series engines) Superior* Worthington*
HDAX 6500 LFG Gas Engine Oil SAE 40			CG gas engines type CG260, CG170 & CG132; Series G3500 [^] & G3400 [^] engines; Proof of Performance gained during extensive field trials in Caterpillar engines [^]	QSV landfill gas engines			TA 1000-1109 for the following fuel class B (biogas, sewage gas) & C (landfill gas) engines: Type 2 & 3, Type 4 A, Type 4 B/D and Type 6 C/E	TCG series gas engines	61-0-0281.1 for fuel types L (landfill), B (biogas) & S (sewage gas)	Engines (landfill gas applications) [^]		MAN Truck & Bus M 3271-4 (special gas)
HDAX 5200 Low Ash Gas Engine Oil SAE 40			CG gas engines type CG260, CG170 & CG132; Series G3600* & G3500* engines		Category I*, II* & III*		TA 1000-1109 for the following engines (including those fitted with an oxidation catalytic converter): Type 2 & 3 (fuel class A), Type 4 A (fuel class A), Type 4 B/D (fuel classes A/B/C), Type 4 C/E (fuel classes A/B/C), Type 6 C/E (fuel class A) and Type 6 F/J (fuel classes A/B/C; Special gas applications) (fuel class S)	TCG series gas engines	61-0-0281.1 for fuel types G (natural gas) & P (propane/butane)	Gas engines & dual fuel engines with natural gas as main fuel	Cogeneration applications; 220GL	Delaval Enterprise* Deutz TR 0199-99-01213 (913, 914 & TCG 2015 series engines) Everlence (MAN Energy Solutions) four-stroke medium speed engines operating on natural gas (LNG, CNG) Superior* Worthington four-stroke*
HDAX 5200 Low Ash Gas Engine Oil SAE 30			Series G3600* & G3500* engines		Category I*, II* & III*							Delaval Enterprise* Superior* Worthington four-stroke*



Black Pearl SRI 2	DIN 51502: K2 N-30* ISO 6743-9: L-XC(L)DFA-2*											
Marfak Bio EliteSyn HD 2	DIN 51502: KPE2 K-40* ISO 12924: L-XD(F)BIB-2*	Swedish Standard (RISE listing) SS 15 54 70 VIDA VGP 2013 compliant (meets EPA Vessel General Permit requirements for environmentally acceptable lubricants)										



Delo XLC Antifreeze/Coolant Concentrate, Premixed 40/60		ASTM D6210* TMC RP 364: Type 1*			CES 14439; CES 14603*	TA 1000-0200	TR 2091 GR.2	61-0-0257*	Stationary Diesel Engines [^]			Detroit Diesel DFS 93K217 Deutz DQC CB-14; Stationary Diesel Engines [^] Everlence (MAN Energy Solutions) 175D engines; 4-stroke medium speed engines MaK (Caterpillar)* [Concentrate] MAN Truck & Bus M 324: Type SNF [Premixed 40/60]
Delo XLI Corrosion Inhibitor Concentrate						TA 1000-0200	TR 0199-99-2091/12		32-9011*			Everlence (MAN Energy Solutions) 175D engines; 4-stroke medium speed engines; MAN 28/33D (marine) engines; Everlence 86W D36 5600 engines* MaK (Caterpillar)* MAN Truck & Bus M 248*
EGX Antifreeze/Coolant Concentrate, Premixed 50/50, Premixed 40/60		ASTM D6210*; D3306* UNE 26-361-88/1*				TA 1000-0200*						Alstom [^] Case New Holland MAT 3624*; MAT 3724 [^] CLAAS* Detroit Diesel DFS 93K217* Deutz DQC CB-14 JCB STD0088* John Deere Power Systems* Kobelco [^] Komatsu KES 07.862 [^] MAN Truck & Bus M 324: Type SNF [^] [Concentrate, Premixed 40/60] Mitsubishi Heavy Industry [^] Perkins engines* Thermo King [^] Vestas Wind Systems [^] Voith* Yanmar [^]

texacolubricants.com/PDS

[^] **GB:** In Chevron's opinion the product is suitable for use in applications where a product of this specification is required. **NL:** Chevron is van mening dat het product geschikt is voor gebruik in toepassingen die een product met deze specificatie vereisen. **F:** Selon Chevron, le produit convient pour une utilisation dans des applications où un produit de cette spécification est exigé. **DE:** Nach Auffassung von Chevron ist das Produkt empfehlenswert und eignet sich zur Verwendung, sofern ein Produkt dieser Spezifikation erforderlich ist. **IT:** Secondo il parere tecnico di Chevron, il prodotto è indicato per l'uso in applicazioni che richiedono una tale specifica. **PL:** Chevron zaleca – w opinii firmy Chevron produkt jest odpowiedni do zastosowania w miejscach, gdzie produkt o tej specyfikacji jest wymagany. **RU:** По мнению специалистов Chevron, данный продукт подходит для применения, где требуется продукт с указанными техническими характеристиками.

* **GB:** Performance – product is either (i) not currently formally approved or certified by the OEM or Industry Standard Organisation; (ii) self-certified; or (iii) was formally approved against an OEM specification which is now obsolete. However, in Chevron's opinion the product is recommended and suitable for use in applications where a product of this specification is required. **NL:** Prestaties – het product is (i) momenteel niet formeel goedgekeurd of gecertificeerd door de OEM of industriestandaardorganisatie; (ii) door Chevron gecertificeerd; of (iii) is eerder goedgekeurd voor een OEM-specificatie die niet meer geldig is. Chevron is echter van mening dat dit product aan te bevelen en geschikt is voor toepassingen waarvoor een product met deze specificatie is vereist. **F:** Performances – le produit (i) est soit actuellement non approuvé ou non certifié officiellement par le fabricant d'équipement d'origine (OEM) ou l'organisation de normalisation (ISO), (ii) soit auto-certifié, ou (iii) a été officiellement déclaré conforme à une spécification du constructeur désormais obsolète. Toutefois, selon Chevron, le produit est recommandé et adapté pour une utilisation dans des applications où un produit présentant ce type de caractéristiques techniques est exigé. **DE:** Leistung – das Produkt (i) besitzt derzeit keine formale OEM- oder Industriestandard-Freigabe; (ii) besitzt eine Eigenzertifizierung; oder (iii) hat früher eine OEM-Freigabe besessen, die mittlerweile aber obsolet ist. Nach Auffassung von Chevron ist das Produkt jedoch empfehlenswert und eignet sich zur Verwendung, sofern ein Produkt dieser Spezifikation erforderlich ist. **IT:** Livello di prestazioni – il prodotto (i) non è al momento attuale approvato o omologato formalmente dal Costruttore o secondo lo Standard Internazionale; (ii) è autocertificato; oppure (iii) è stato approvato formalmente rispetto alla specifica del Costruttore, che però risulta al momento attuale obsoleta. Tuttavia, secondo il parere tecnico di Chevron il prodotto è raccomandato e adatto all'uso in applicazioni che richiedono una tale specifica. **PL:** Normy i zatwierdzenia – produkt (i) nie posiada jeszcze formalnego zatwierdzenia lub certyfikacji producentów oryginalnego sprzętu lub branżowej organizacji normalizacyjnej; (ii) deklaracja producenta; lub (iii) był formalnie zatwierdzony wg specyfikacji OEM, która jest obecnie nieaktualna. W opinii Chevron produkt jest jednak zalecany i odpowiedni do użytku w zastosowaniach, w których wymagany jest produkt o tej specyfikacji. **RU:** Эксплуатационные характеристики – данный продукт (i) в настоящее время официально не одобрен или не подтвержден производителем оборудования (OEM); или организацией по промышленной стандартизации; или (ii) подтвержден самостоятельно; или (iii) был официально одобрен по спецификации производителя оборудования (OEM), которая в настоящий момент устарела. Однако, по мнению специалистов Chevron, данный продукт может быть рекомендован для применения, где требуется продукт с указанными техническими характеристиками.

GB: For backward compatibility of products, refer to PDS: texacolubricants.com/PDS **NL:** Raadpleeg voor achterwaartse compatibiliteit van producten het PDS: texacolubricants.com/PDS **F:** Pour plus d'informations sur la rétrocompatibilité des produits, veuillez vous reporter aux fiches techniques disponibles : texacolubricants.com/PDS **DE:** Hinweise zur Rückwärtskompatibilität finden Sie im Produktdatenblatt unter: texacolubricants.com/PDS **IT:** Per la retrocompatibilità dei prodotti, fare riferimento alle PDS: texacolubricants.com/PDS **PL:** Informacje na temat kompatybilności wstecznej produktów znaleźć można w kartach charakterystyki: texacolubricants.com/PDS **RU:** Для получения дополнительной информации о совместимости продуктов с предыдущими версиями, обратитесь к технической спецификации продукта (PDS) по ссылке: texacolubricants.com/PDS